

CHAIN SPECIFICATIONS

MX/OFF-ROAD / ATV / STREET

Model	Recommended Uses	Color	Ring Type	Master Link Type	Tensile Strength (lbs)	Weight (lbs per 100 links)	Pin Length (mm)	Max cc Off-Road/Street
HEAVY DUTY								
520HDN	Off-Rd / MX	N	None	Clip	7850	3.15	18.15	250 / NA
520SSR	ATV, Off-Rd / MX, Street	N	O-ring	Clip	7670	4.08	19.90	400 / 400
520RDG	Street	N	DG	Rivet	8490	3.36	19.90	750 / 750
525RDG	Street	N	DG	Rivet	8820	4.30	22.85	750 / 900
530RDG	Street	N	DG	Rivet	9480	4.48	24.90	750 / 1000
WORKS								
420MXR	Off-Rd / MX	G	None	Clip	4980	1.76	15.70	150 / 150
428MXR	Off-Rd / MX	G	None	Clip	5780	2.13	17.60	150 / 250
520MXRI	Off-Rd / MX	G	None	Clip	8970	2.99	17.70	500 / NA
520XTG	ATV, Off-Rd / MX	G	TG	Clip	8460	3.36	20.80	750 / 400
520RTGI	Street	G	TG	Rivet	9270	3.75	22.85	750 / 1000
530RTGI	Street	G	TG	Rivet	9900	4.63	24.90	900 / 1400

Color: N - Natural | G - Gold / Ring Type: DG - DualGuard | TG - TripleGuard

SUNSTAR MANUFACTURER RECOMMENDATIONS

All chains should be installed by a certified mechanic, using the proper installation tools. Chain adjustment should be per the motorcycle manufacturer's owner's manual.

Always check sprocket alignment when installing new drive components and during routine maintenance and adjustment; mis-aligned sprockets are detrimental in reducing the life of the entire drive system.

It is recommended to replace your chain with the same size and type of chain that originally came on the motorcycle.

Avoid using volatile solvents such as gasoline, thinners and/or benzine - It is best to consult with your local dealer before using cleaners or lubes.

For best results and life, replace chain and sprockets together with Sunstar brand components.